

Specifications:**Material And Finish:**

Insulator:Nylon 6T UL94V-0 Color:Black

Contact:Brass

Plated:See Ordering Information

Rating:

Current Rating:1.0 Amp

Voltage Rating:100V AC/DC

Operating Temperature Range:-40~+105°C

Electrical:

Contact resistance:20m Ohm Max





Insulator resistance:500M ohm min.

Withstanding Voltage:500V AC/Minute


Ordering Information**12772M-XXA056-NX**

1 2 3 4 5

- 1:— Series No.
2:— M:SMT Type
3:— No. of Positions
4:— A:Gold Flash
5:— B:In Tube
F:W/Cap In Tape&Reel



Recommended PCB Layout

5X				DR.BY.: Aaron	GENERAL TOLERANCE:		PART NO : 12772M-XXX056-NX	HJBRIGHT 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED	
4X					LINEAR	ANGLES	DWG. NO.:		
3X				CHKD.: Tony	X.: ±0.30	X': ±5.0°	TITLE :	SHEET: 1/1	 THIRD ANGLE PROJECTION
2X	Update lid size	Judyyan	20220707	APPD.: Billy	X.X: ±0.20	X.X': ±3.0°	1.27mm Pitch Pin Header SMT Type	SCALE: 1:1	
1X	ORIGINAL	Aaron			X.XX: ±0.15	X.XX': ±2.0°	DATE: 05-May-2019	UNIT: mm	
REV.	DESCRIPTION	DR.BY	ECN. NO.		X.XXX: ±0.10	X.XXX': ±1.0°			A4