


Plated:See Ordering Information

Operating Temperature Range: $-40^{\circ}\sim+105^{\circ}\text{C}$

Withstanding Voltage:500V AC/Minute

$$\overline{1} \quad \overline{2} \quad \overline{3} \quad \overline{4} \quad \overline{5}$$


Recommended PCB Layout(Tolerance:0.05mm)

				DR.BY.: Kenry	GENERAL TOLERANCE:		PART NO : 12782S-XXX072-NX		HJBRIGHT® 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED			
					LINEAR	ANGLES	DWG. NO.:					
				CHKD.: Tony	x.: ±0.30	x': ±5.0°	TITLE : 1.27mm Pitch Pin Header Straight Type		SHEET: 1/1		A4	
					x.x: ±0.20	x.x': ±3.0°			SCALE: 1:1			
				APPD.: Billy	x.xx: ±0.15	x.xxx: ±2.0°			UNIT: mm			THIRD ANGLE PROJECTION
1X	ORIGINAL	Kenry			x.xxx: ±0.10	x.xxx': ±1.0°	DATE: 17-JNA-2022					
REV.	DESCRIPTION	DR.BY	ECN. NO.									