

RoHS Compliant

Specifications:

Material And Finish:

Insulator:Nylon 6T UL94V-0 Color:Black

Contact:Brass

Plated:See Ordering Information

Rating:

Current Rating:2.0 Amp

Voltage Rating:150V AC/DC

Operating Temperature Range:-40~+105°C

Electrical:

Contact resistance:20m Ohm Max

Insulator resistance:1000M ohm min.





Withstanding Voltage:500V AC/Minute

Ordering Information

20022S-XXX078-NX

1 2 3 4 5

- 1:— Series No.
2:— S:Straight Type
3:— No. of Positions
4:— A:Gold Flash
D:Gold 10u"
H:Selective Gold Plated
Q:Tin Plated
5:— A:In bag
B:In Tube
C:In Tray



Recommended PCB Layout

DR.BY.: Judyyan	GENERAL TOLERANCE:		PART NO : 20022S-XXX078-NX		HJBRIGHT® 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED		
	LINEAR	ANGLES	DWG. NO.:				
CHKD.: Kenry	x.: ±0.30	x': ±5.0°	TITLE : 2.0mm Pitch Pin Header Straight Type		SHEET: 1/1		A4
	x.x: ±0.20	x.x': ±3.0°			SCALE: 1:1		
APPD.: Billy	x.xx: ±0.15	x.xx': ±2.0°			UNIT: mm		
	x.xxx: ±0.10	x.xxx': ±1.0°	DATE: 08-Sep-2025	THIRD ANGLE PROJECTION			

1X	ORIGINAL	Judyyan	ECN. NO.
REV.	DESCRIPTION	DR.BY	