

Specifications:**Material And Finish:**

Insulator:Nylon 6T UL94V-0 Color:Black

Contact:Phosphor Bronze

Plated:See Ordering Information

Rating:

Current Rating:1.0 Amp

Voltage Rating:100V AC/DC

Operating Temperature Range:-40° ~+125° C

Electrical:

Contact resistance:20m Ohm Max




Insulator resistance:500M ohm min.

Withstanding Voltage:500V AC/Minute

Ordering Information**S12711R-XXX34-NX**

1 2 3 4 5

- 1: — Series No.
2: — R/R/A Type
3: — No. of Positions
4: — A:Gold Flash
H:Selective Gold Plated
Q:Tin Plated
5: — A:In bag
B:In Tube
C:In Tray
D:In Tape&Reel



Recommended PCB Layout

5X				DR.BY.: Samson	GENERAL TOLERANCE:		PART NO : S12711R-XXX34-NX	HJBRIGHT[®] 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED A4		
4X					LINEAR	ANGLES	DWG. NO.: RD0306-113			
3X				CHKD.: Tony	x.: ±0.30	x': ±5.0°	TITLE : 1.27mm Pitch PCB Socket Header R/A Type			
2X					x.x: ±0.20	x.x': ±3.0°				
1X	ORIGINAL	joy chen		APPD.: Billy	x.xx: ±0.15	x.xx': ±2.0°		SHEET: 1/1	THIRD ANGLE PROJECTION	
REV.	DESCRIPTION	DR.BY	ECN. NO.		x.xxx: ±0.10	x.xxx': ±1.0°	DATE: 28-Jun-2008	SCALE: 1:1		
							UNIT: mm			