

Specifications:

Material And Finish:

Insulator:PA6T UL94V-0 Color:Black
 Contact:Phosphor Bronze
 Plated:See Ordering Information

Rating:

Current Rating:2.0 Amp
 Voltage Rating:150V AC/DC
 Operating Temperature Range:-40~+105°C

Electrical:





Contact resistance:20m Ohm Max
 Insulator resistance:1000M ohm min.
 Withstanding Voltage:500V AC/Minute

Ordering Information

S20032M-XXX43-NX

1 2 3 4 5

- 1: — Series No.
- 2: — M:SMT Type
- 3: — No. of Positions(4-50PIN)
- 4: — A:Gold Flash
 Q:Tin Plated
 M:Matte TIN
- 5: — E:W/Cap In Tube
 F:W/Cap In Tape&Reel




Recommended PCB Layout(Tolerance:0.05mm)

5X				DR.BY.: Aaron	GENERAL TOLERANCE:		PART NO : S20032M-XXX43-NX	
4X					LINEAR	ANGLES	DWG. NO.:	
3X				CHKD.: Tony	x.: ±0.30	x': ±5.0°	TITLE : 2.0mm Pitch Socket Header SMT Type	
2X				APPD.: Billy	x.x: ±0.20	x.x': ±3.0°	DATE: 11-May-2018	
1X	ORIGINAL	Aaron			x.xx: ±0.15	x.xx': ±2.0°		
REV.	DESCRIPTION	DR.BY	ECN. NO.		x.xxx: ±0.10	x.xxx': ±1.0°		

HJBRIGHT 東莞市華晶電子有限公司
 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

SHEET: 1/1
 SCALE: 1:1
 UNIT: mm



THIRD ANGLE PROJECTION

A4