

Specifications:**Material And Finish:**

Insulator:PA6T UL94V-0 Color:Black

Contact:Phosphor Bronze

Plated:See Ordering Information

Rating:

Current Rating:3.0 Amp

Voltage Rating:250V AC/DC

Operating Temperature Range:-40°~+105°C

Electrical:

Contact resistance:20m Ohm Max





Insulator resistance:1000M ohm min.

Withstanding Voltage:500V AC/Minute

Ordering Information**S25442S-XXX85-5AX**

1 2 3 4 5 6

- 1: — Series No.
2: — S: Straight Type
3: — No. of Positions
4: — A: Gold Flash
H: Selective Gold Plated
Q: Tin Plated
5: — 5: W/Bump
6: — A: In bag
B: In Tube
C: In Tray



Recommended PCB Layout

5X				DR.BY.:	GENERAL TOLERANCE:		PART NO : S25442S-XXX85-5AX		HJBRIGHT® 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED						
4X				Samson	LINEAR	ANGLES	DWG. NO.:								
3X				CHKD.:	x.: ±0.30	x': ±5.0°	TITLE : 2.54mm Pitch PCB Socket Header Straight Type		SHEET: 1/1			A4			
2X				Tony	x.x: ±0.20	x.x': ±3.0°			SCALE: 1:1						
1X	ORIGINAL	Samson		APPD.:	x.xx: ±0.15	x.xx': ±2.0°	DATE: 12-JUL-2008		UNIT: mm				THIRD ANGLE PROJECTION		
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	x.xxx: ±0.10	x.xxx': ±1.0°									
1		2		3		4		5		6		7		8	