

Material And Finish:

Contact:Phosphor Bronze

Plated:Gold Pated

Rating:

Current Rating:1.5 Amp

Voltage Rating: 125V AC/DC

Operating Temperature Range: $-40^{\circ}\sim+105^{\circ}\text{C}$

Electrical:

Contact resistance:20m Ohm Max

Insulator resistance:500M ohm min.

Withstanding Voltage:500V AC/Minute

Mechanical:

Durability:750 Cycles Min

Ordering Information

MJ004R-8PXCX-1X

$$\overline{1} \quad \overline{2} \quad \overline{3} \quad \overline{4} \quad \overline{5} \quad \overline{67}$$

1: — Series No.

2:—R:R/A Type

3:—No. of Positions

4:—No. of Contact:

8:8 Contacts

6:6 Contacts

4:4 Contacts

2:2 Contacts

5:—B:Gold Plated $3\mu''(0.075\mu m)$

C:Gold Plated $6\mu''(0.15\mu m)$

D:Gold Plated $10\mu''(0.25\mu m)$

F:Gold Plated 15 μ "(0.375 μ m)

G: Gold Plated $.30\mu"$ ($0.75\mu\text{m}$)

-1: Without Flange

7: — Δ : In bag

A: In bag
 B: In Tube

C:In Tray

Recommended PCB Layout Tolerance: ± 0.05

5X				DR.BY.:	GENERAL TOLERANCE:		PART NO : MJ004R-8PXCX-1X	HJBRIGHT® 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED		
4X				Samson	LINEAR	ANGLES	DWG. NO.: RD0810-001			
3X				CHKD.:	x.: ±0.30	x*: ±5.0°	TITLE : 8PXC Modular jack R/A Type	SHEET: 1/1		A4
2X				Tony	x.x: ±0.20	x.x*: ±3.0°		SCALE: 1:1		
1X	ORIGINAL	Samson		APPD.:	x.xx: ±0.15	x.xx*: ±2.0°		UNIT: mm		
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	x.xxx: ±0.10	x.xxx*: ±1.0°	DATE: 10-Oct-2008			