


Plated: See Ordering Information

Operating Temperature Range: $-40^{\circ}\sim+105^{\circ}\text{C}$

Withstanding Voltage:500V AC/Minute

$$\overline{1} \quad \overline{2} \quad \overline{3} \quad \overline{4} \quad \overline{5}$$

- 1:— Series No.
2:— R:R/A Type
3:— No. of Positions
4:— A:Gold Flash
H:Selective Gold
Q:Tin Plated
5:— A:In bag
B:In Tube
C:In Tray



Recommended PCB Layout

5X			DR.BY.: joy chen	GENERAL TOLERANCE:		PART NO : 254122R-XXXXXX-X		HJBRIGHT[®] 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED			
4X				LINEAR	ANGLES	DWG. NO.: RD0807-204					
3X			CHKD.: Tony	x.: ±0.30	x': ±5.0"	TITLE : 2.54mm Pitch Pin Header R/A Type		SHEET: 1/1			A4
2X				x.x: ±0.20	x.x': ±3.0"			SCALE: 1:1			
1X	ORIGINAL	joy chen	APPD.: Billy	x.xx: ±0.15	x.xx': ±2.0"	DATE: 21-Jul-2008		UNIT: mm			
REV.	DESCRIPTION	DR.BY	ECN. NO		x.xxx: ±0.10	x.xxx': ±1.0"					