

Specifications:

Material And Finish:

Insulator:PA6T UL94V-0 Color:Black

Contact:Brass

Rating:

Current Rating:2.0 Amp

Voltage Rating:150V AC/DC

Operating Temperature Range:-55~+125°C

Electrical:

Contact resistance:20m Ohm Max

Insulator resistance:5000M ohm min.

Withstanding Voltage:500V AC/Minute

Ordering Information

200122M-XXX190-NXX

1 2 3 4 56

1: Series No.

2: SMT Type

3: No. of Positions

4: A:Gold Flash

H:Contact Plated Gold Flash;

Other area plated matte tin

T:10u" Gold on contact;Matte Tin on tail





Q:Tin Plated

5: 0:W/O Peg

1:W/Peg

6: E:W/Cap In Tube

F:W/Cap In Tape&Reel



Recommended PCB Layout(Tolerance:±0.05mm)

5X			
4X			
3X			
2X			
1X	ORIGINAL	Aaron	
REV.	DESCRIPTION	DR.BY	ECN. NO.

DR.BY:	Aaron
CHKD.:	Tony
APPD.:	Billy

GENERAL TOLERANCE:		PART NO : 200122M-XXX190-NXX
LINEAR	ANGLES	DWG. NO.:
x.: ±0.30	x': ±5.0°	TITLE :
x.x: ±0.20	x.x': ±3.0°	2.0mm Pitch Pin Header SMT Type
x.xx: ±0.15	x.xx': ±2.0°	DATE: 23-Jan-2018
x.xxx: ±0.10	x.xxx': ±1.0°	

HJBRIGHT 東莞市華晶電子有限公司
BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

SHEET: 1/1
SCALE: 1:1
UNIT: mm

THIRD ANGLE PROJECTION

A4