

Specifications:

Material And Finish:

Insulator:Nylon 6T UL94V-0 Color:Black

Contact:Brass

Plated:See Ordering Information

Rating:

Current Rating:1.0 Amp

Voltage Rating:100V AC/DC

Operating Temperature Range:-40~+105°C

Electrical:

Contact resistance:40m Ohm Max

Insulator resistance:500M ohm min.

Withstanding Voltage:500V AC/Minute

Ordering Information




B1002M-XXX-01-1X

1 2 3 4 5

- 1: — Series No.
2: — M:SMT Type
3: — No. of Positions
4: — A:Gold Flash
H:Selective Gold Plated
Q:Tin Plated
6: — A:In bag
B:In Tube
F:W/Cap In Tape&Reel

RoHS Compliant

5X				DR.BY.:	GENERAL TOLERANCE:		PART NO : B1002M-XXX-01-1X		HJBRIGHT® 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED		
4X				Samson	LINEAR		DWG. NO.: RD0805-040				
3X				CHKD.:	x.: ±0.30	x°: ±5.0°	TITLE : 1.0mm Pitch Box Header SMT Type		SHEET: 1/1		A4
2X				Tony	x.x: ±0.20	x.x°: ±3.0°			SCALE: 1:1		
1X	ORIGINAL	Samson		APPD.:	x.xx: ±0.15	x.xx°: ±2.0°			UNIT: mm		
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	x.xxx: ±0.10	x.xxx°: ±1.0°	DATE: 12-May-2008				



Recommended PCB Layout

