

Specifications:**Material And Finish:**

Insulator:PA6T UL94V-0 Color:Black

Contact:Phosphor Bronze

Plated:See Ordering Information

Rating:

Current Rating:1.0 Amp

Voltage Rating:100V AC/DC

Operating Temperature Range:-40° ~+105° C

Electrical:

Contact resistance:20m Ohm Max


Insulator resistance:500M ohm min.

Withstanding Voltage:500V AC/Minute

Ordering Information**S12722M-XXX43-5ANX**

1 2 3 4 5 6 7

- 1: — Series No.
2: — M:SMT Type
3: — No. of Positions
4: — A:Gold Flash
H:Selective Gold Plated
Q:Tin Plated
5: — 5:W/Bump
6: — A:Registration Mast
7: — A:In bag
B:In Tube
C:In Tray
E:Mylar In Tape&Reel
F:W/Cap In Tape&Reel



5X				DR.BY.:	GENERAL TOLERANCE:		PART NO : S12722M-XXX43-5ANX		HJBRIGHT 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED		
4X				Kenry	LINEAR	ANGLES	DWG. NO.:				
3X				CHKD.:	x.: ±0.30	x': ±5.0°	TITLE : 1.27mm Pitch PCB Socket Header SMT Type		SHEET: 1/1		A4
2X				Tony	x.x: ±0.25	x.x': ±3.0°			SCALE:1:1		
1X	ORIGINAL	Kenry		APPD.:	x.xx: ±0.15	x.xx': ±2.0°	DATE: 20-Apr-2015		UNIT:mm		
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	x.xxx:	x.xxx': ±1.0°					