

Specifications:

Material And Finish:

Insulator:PBT UL94V-0 Color:Black

Contact:Brass

Plated:See Ordering Information

Rating:

Current Rating:10.0 Amp

Voltage Rating:250V AC/DC

Operating Temperature Range:-40°~+105°C

Electrical:

Contact resistance:20m Ohm Max

Insulator resistance:1000M ohm min.

Withstanding Voltage:2000V AC/Minute

Ordering Information

A400005R-35X-XX-C

1 2 3 4 5 6

1:—Series No.

2:—R/R/A Type

3:—No. of Positions

4:—A:Gold Flash

F:20u" Gold on Contact;Gold Flash on all

G:20u" Gold on Contact;Matte Tin on tail

H:Gold Flash on Contact;Matte Tin on tail




S:Matte Tin Plated

5:—01:A Type Black


02:B Type Natural

03:D Type Blue


6:—C:In Tray




SEC A-A



A Type Black



B Type white



D Type Blue

5X			
4X			
3X	Update type option	Anne	20241101
2X	Update code option	DENG	20230410
1X	ORIGINAL	Kenry	
REV.	DESCRIPTION	DR.BY	ECN. NO.


DR.BY.:	Kenry
CHKD.:	Tony
APPD.:	Billy

GENERAL TOLERANCE:	
LINEAR	ANGLES
X.: ±0.30	X': ±5.0°
X.X: ±0.20	X.X': ±3.0°
X.XX: ±0.15	X.XX': ±2.0°
X.XXX: ±0.10	X.XXX': ±1.0°

PART NO : A400005R-35X-XX-C
DWG. NO.:
TITLE : 4.00mm Pitch Header Assembly, R/A Type
DATE: 19-Jan-2015

HJBRIGHT® 東莞市華晶電子有限公司
BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

SHEET: 1/1
SCALE: 1:1
UNIT: mm



THIRD ANGLE PROJECTION

A4