



Notes:

1. Connector must be mounted $90^{\circ} \pm 1^{\circ}$ to Cable.
2. Ensure connectors are installed fully seated.
3. Adjacent conductors must not be shorted
4. Trim cable flush with connectors ensuring ends of conductors are not frayed.

Ordering Information
C2542-XXQ-XXX-03
1 2 3


- 1: — Series No.
2: — No. of Positions
04: 2*2PIN
06: 2*3PIN
.....
26: 2*13PIN
3: — Wire Length
105: L=105mm
110: L=110mm
.....

2	Cable Wire	UL2651 28AWG PH1.27mm 105°C 300V VW-1	Wenchang	PER DESCRIPTION	1PCS
1	IDC	2.54mm Pitch IDC 2*N Red	BRIGHT	DP2541-XXQ-01-A	2PCS
ITEM	Part name	Description	Manufacturer	Manufacturer P/N	Color QTY

DR.BY.: Judyyan	GENERAL TOLERANCE:		PART NO : C2542-XXQ-XXX-03	
CHKD.: Tony	LINEAR	ANGLES	DWG. NO.:	
	1~150: ± 3	X: $\pm 5.0^{\circ}$	TITLE :	
	150~300: ± 5	X.X: $\pm 3.0^{\circ}$	CABLE ASSY, Micro-Match MOW-MOW	
APPD.: Billy	300~450: ± 10	X.XX: $\pm 2.0^{\circ}$	DATE: 1-Nov-2024	
		X.XXX: $\pm 1.0^{\circ}$		

HJBRIGHT® 東莞市華晶電子有限公司
BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

SHEET: 1/1
SCALE: 1:1
UNIT: mm



THIRD ANGLE PROJECTION

A4

1X	ORIGINAL	Judyyan	ECN. NO.
REV.	DESCRIPTION	DR.BY	