

RoHS Compliant

Specifications:

Material And Finish:

Insulator:PBT UL94V-0
Contact:Brass
Shell:Steel With Nickel Plated.
Plated:See Ordering Information

Rating:

Current Rating:5.0 Amp
Operating Temperature Range:-55~+105°C

Electrical:

Contact resistance:30m Ohm Max
Insulator resistance:5000M ohm min.
Withstanding Voltage:1000V AC/Minute

Ordering Information

DB07S-XXFX-XX-XC


1 2 3 4 5 6 7 8

1:— Series No.
2:— S: Straight Type
3:— No. of Positions
4:— F: FeMale
5:— 5: Selective Gold Plated
6:— 01: With stud
02: Without stud
7:— Color:
B: Black
W: White
BL: Blue
8:— C: In Tray

01: With stud

02: Without stud

Pin	A	B	C	D
09	16.30	24.99	30.80	19.30
15	24.60	33.30	39.20	27.60
25	38.30	47.04	53.10	41.10
37	54.80	63.50	69.34	57.30

5X				DR.BY.: Jack	GENERAL TOLERANCE:		PART NO : DB07S-XXFX-XX-XC	HJBRIGHT® 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED		
4X				Jack	LINEAR	ANGLES	DWG. NO.:			
3X	Update code options	Judyyan	20220802	CHKD.: Kenry	X.: ±0.38	X': ±5.0°	TITLE : D-SUB FeMale Straight Type	SHEET: 1/1	 THIRD ANGLE PROJECTION	A4
2X	變更螺柱高度	Aaron	20170721	APPD.: Billy	X.X: ±0.35	X.X': ±3.0°	DATE: 3-Mar-2015	SCALE: 1:1		
1X	ORIGINAL	Jack			X.XX: ±0.25	X.XX': ±2.0°		UNIT: mm		
REV.	DESCRIPTION	DR.BY	ECN. NO		X.XXX: ±0.13	X.XXX': ±1.0°				

Plated:See Ordering Information

Operating Temperature Range: $-55^{\circ}\sim+105^{\circ}\text{C}$


Withstanding Voltage:1000V AC/Minute

1	2	3	4	5	6	7	8
---	---	---	---	---	---	---	---

- 1: — Series No.
2: — S: Straight Type
3: — No. of Positions
4: — F: FeMale
5: — 5: Selective Gold Plated
6: — 01: With stud
 02: Without stud
7: — Color:
 B: Black
 W: White
 BL: Blue
8: — C: In Tray



Pin	A	B	C	D
09	16.30	24.99	30.80	19.30
15	24.60	33.30	39.20	27.60
25	38.30	47.04	53.10	41.10
37	54.80	63.50	69.34	57.30

5X				DR.BY.: Jack	GENERAL TOLERANCE:		PART NO : DB07S-XXFX-XX-XC		HJBRIGHT® 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED			
4X						LINEAR	ANGLES	DWG. NO.:				
3X	Update code options	Judyyan	20220802	CHKD.: Kenry	x.: ±0.38	x": ±5.0"	TITLE : D-SUB FeMale Straight Type		SHEET: 1/1			A4
2X	變更螺柱高度	Aaron	20170721		x.x: ±0.35	x.X": ±3.0"			SCALE: 1:1			
1X	ORIGINAL	Jack		APPD.:	x.XX: ±0.25	x.XX": ±2.0"	DATE: 3-Mar-2015		UNIT: mm			
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	x.XXX: ±0.13	x.XXX": ±1.0"						