



Specifications:

Material And Finish:

Insulator:Nylon 9T UL94V-0

Color:See Ordering Information

Rating:

Current Rating:5.0 Amp

Voltage Rating:100V AC/DC

Operating Temperature




Range:—40°~+125°C

Electrical:

Contact resistance:15m Ohm Max

Insulator resistance:100M ohm min.



Withstanding Voltage:1000V AC/Minute



Ordering Information
H2028MR—02P—01—XA
1 2 3 4 5
1:— Series No.
2:— R:R/A Type
3:— No. of Positions
4:— A:A Type Black
B:B Type Nature
5:— A:n Bag

A type Black

B type Nature



HUBRIGHT® 東莞市華晶電子有限公司

BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

TITLE : 2.0mm Pitch ULH Series 2Pin Female
connector / Right angle up

SHEET: 1/1
SCALE: 1:1



THIRD ANGLE PROJECTION

A4

5X				DR.BY: Zolin
4X				
3X				CHKD: Hu.CH
2X				
1X	ORIGINAL	Zolin		APPD:
REV	DESCRIPTION	DR.BY	ECN. NO.	Billy

GENERAL TOLERANCE:	
LINEAR	ANGLES
X.: ±5.0°	X.: ±5.0°
XX: ±0.30	XX: ±3.0°
XXX: ±0.30	XXX: ±2.0°
XXXX: ±0.15	XXXX: ±1.0°

PART NO : H2028MR—02P—01—XA
DWG. NO.:
DATE: 04—Dec—2025

UNIT: mm
