







Specifications:
Material And Finish:
Insulator:Nylon 9T UL94V-0
Color:See Ordering Information

Rating:
Current Rating:5.0 Amp
Voltage Rating:100V AC/DC
Operating Temperature
Range:-40°~+125°C

Electrical:
Contact resistance:15m Ohm Max
Insulator resistance:100M ohm min.
Withstanding Voltage:1000V AC/Minute



Ordering Information
H2028MR-04P-02-XA

1 2 3 4 5



- 1: — Series No.
- 2: — R:R/A Type
- 3: — No. of Positions
- 4: — A:A Type Black
B:B Type Nature
C:C Type Blue
D:D Type Red
- 5: — A:I:n Bag

A type Black

B type Nature

C type Blue

D type Red



HUBRIGHT® 東莞市華晶電子有限公司

BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

TITLE : 2.0mm Pitch ULH Series 4Pin Female
connector / Right angle down

SHEET: 1/1
SCALE: 1:1



THIRD ANGLE PROJECTION

A4

DR.BY: Zolin

GENERAL TOLERANCE:
LINEAR ANGLES

PART NO : H2028MR-04P-02-XA
DWG. NO.:

DATE: 05-Dec-2025

UNIT: mm

REVISION

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15

X.XXX: ±1.0'

X.X: ±0.30

X.X: ±3.0'

X.X: ±5.0'

CHKD: Hu.CH

3X

2X

1X

REV

DESCRIPTION

DR.BY

ECN. NO.

APPD.

Billy

X.XXX: ±0.15