

RoHS Compliant



Automobile
Product

Specifications:

Material And Finish:

Insulator:Nylon 9T UL94V-0

Color:See Ordering Information

Rating:

Current Rating:5.0 Amp

Voltage Rating:100V AC/DC

Operating Temperature

Range:-40°~+125°C

Electrical:

Contact resistance:15m Ohm Max

Insulator resistance:100M ohm min.

Withstanding Voltage:1000V AC/Minute

Ordering Information

H2028MS-04P-01-XA

1 2 3 4

1: — Series No.

2: — S: Straight Type




3: — No. of Positions

4: — A: A Type Black

B: B Type Nature

C: C Type Blue

D: D Type Red



A type Black


C type Blue



B type Nature

D type Red



5X				DR.BY.:	GENERAL TOLERANCE:		PART NO : H2028MS-04P-01-XA		HJBRIGHT® 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED			
4X				Zolin	LINEAR	ANGLES	DWG. NO.:					
3X				CHKD.:	x.:	x': ±5.0°	TITLE : 2.0mm Pitch ULH Series 4Pin Female connector / Straight Type		SHEET: 1/1			A4
2X				Hu.CH	x.x: ±0.30	x.x': ±3.0°			SCALE: 1:1			
1X	ORIGINAL	Zolin		APPD.:	x.xx: ±0.30	x.xx': ±2.0°	DATE: 05-Dec-2025		UNIT: mm			
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	x.xxx: ±0.15	x.xxx': ±1.0°						