

Specifications:**Material And Finish:**

Insulator:PBT,UL94V-0

Rating:

Current Rating:7 Amp(18AWG)

Voltage Rating:300V AC/DC


Operating Temperature Range:-40°C~+105°C

Electrical:

Contact resistance:10m Ohm Max

Insulator resistance:1000M Ohm min.

Withstanding Voltage:1500V AC/Minute

**Ordering Information****H5004F-XXP-02-A**


1 2 3 4

1: — Series No.


2: — F:Female

3: — No. of Positions

4: — A:In Bag



No.	Dimension mm	
	A	B
2	—	14.2
3	10.0	19.2

5X				DR.BY.:	GENERAL TOLERANCE:		PART NO : H5004F-XXP-02-A	HJBRIGHT® 東莞市華晶電子有限公司 BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED		
4X				Deng	LINEAR	ANGLES	DWG. NO.:			
3X				CHKD.:	X.:	X': ±5.0°	TITLE : 5.0mm Pitch Female	SHEET: 1/1		A4
2X				Aren	X.X: ±0.40	X.X': ±3.0°		SCALE: 1:1		
1X	ORIGINAL	Deng		APPD.:	X.XX: ±0.25	X.XX': ±2.0°		UNIT: mm		
REV.	DESCRIPTION	DR.BY	ECN. NO.	Billy	X.XXX: ±0.15	X.XXX': ±1.0°	DATE: 11-Jul-2021			