

Specifications:

Material And Finish








Insulator: Nylon66, UL94V-V0
Plated: See Ordering Information

Rating:

Current Rating: 10A AC,DC
Voltage Rating: 600V AC/DC
Operating Temperature Range: -25~+85°C

Electrical:

Contact resistance: 3.5m Ohm Max
Insulator resistance: 1000M ohm min.
Withstanding Voltage: 5000V AC/Minute



Ordering Information

H6100-02-G-A

1 2 3 4

- 1: — Series No.
- 2: — No. of Positions
- 3: — G: Green
- 4: — A: In bag

General tolerance SJ1372-78-5

Basic dimensions(mm)	Tol Value (mm)	Basic dimensions(mm)	Tol Value (mm)
0~3	0.16	24~30	0.32
3~6	0.18	30~40	0.36
6~10	0.20	40~50	0.40
10~14	0.22	50~65	0.46
14~18	0.24	65~80	0.52
18~24	0.28	>80	0.60

5X			
4X			
3X			
2X	Update code option	Deng	20230419
1X	ORIGINAL	Wark	
REV.	DESCRIPTION	DR.BY	ECN. NO.

DR.BY:	Wark	
CHKD.:	Ren	
APPD.:	Billy	

GENERAL TOLERANCE:	
LINEAR	ANGLES
X.: ±0.30	X': ±5.0°
X.X: ±0.20	X.X': ±3.0°
X.XX: ±0.15	X.XX': ±2.0°
X.XXX: ±0.10	X.XXX': ±1.0°
PART NO : H6100-02-G	
DWG. NO.:	
TITLE : 6.10mm Pitch Housing	
DATE: 10-Mar-2020	

HJBRIGHT 东莞市华晶电子有限公司
BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

SHEET: 1/1
SCALE: 1:1
UNIT: mm

THIRD ANGLE PROJECTION

A4