

Specifications:

Material And Finish:

Insulator:Nylon 9T UL94V-0 Color:Black

Contact:Phosphor Bronze

Plated:See Ordering Information

Rating:

Current Rating:2.0 Amp

Voltage Rating:150V AC/DC

Operating Temperature Range:-40~+105°C

Electrical:

Contact resistance:20m Ohm Max

Insulator resistance:1000M ohm min.

Withstanding Voltage:500V AC/Minute

Ordering Information

S20012M-XXX22A-XXX

1 2 3 4 567

1:—Series No.

2:—M:SMT Type

3:—No. of Positions

4:—A:Gold Flash

5:—C:LCP

N:PA6T

5:—0:W/O Peg



1:W/Peg

5:—B:In Tube



E:W/Cap In Tube

F:W/Cap In Tape&Reel


M:Mylar In Tape&Reel



0:W/O Peg



1:W/Peg



Recommended PCB Layout

1X	ORIGINAL	Samson	
REV.	DESCRIPTION	DR.BY	ECN. NO.

DR.BY: Samson	GENERAL TOLERANCE:		PART NO : S20012M-XXX22A-XXX
	LINEAR	ANGLES	
CHKD.: Tony	X.: ±0.30	X': ±5.0°	DWG. NO.:
	X.X: ±0.20	X.X': ±3.0°	
APPD.: Billy	X.XX: ±0.15	X.XX': ±2.0°	TITLE : 2.0mm Pitch Socket Header SMT Type
	X.XXX: ±0.10	X.XXX': ±1.0°	
			DATE: 5-Dec-2013

HJBRIGHT® 東莞市華晶電子有限公司
BRIGHT-E ELECTRONIC TECHNOLOGY LIMITED

SHEET: 1/1
SCALE: 1:1
UNIT: mm



THIRD ANGLE PROJECTION

A4